

GlobeHeat Datasheet : Product Code GHT 1232



Product Description: 10.5kW Inverter Power Source (In Mild Steel Case)

Globe's Inverter Power Source is a portable heat treatment unit, designed for powering and controlling standard 60V, 48V or 30V heating elements dependent up on the operator selected maximum output voltage setting.

Applications

For the post weld heat treatment and preheating of pipe welds and welded fabrications where only one control zone is required. Up to eight additional units can be inked where multiple zones are required).

At 17Kg, the inverter's lightweight design is ideal for smaller heat treatment jobs, areas with limited access, or where transportation limitations is an issue.

Features

- Capacity to store up to twenty user defined heat treatment profiles
- Each profile can contain up to nine ramp or hold segments
- Integrated temperature data logger for recording and storing up to 64 hours of data. Stored as a CSV File
- Includes disc containing software and instructions and USB connection cable for data
- Auxiliary thermocouple socket for use with optional external recorder
- Option for manual temperature control via the energy regulator mode
- Will power up to four standard 60V ceramic pad heating elements up to a total maximum power output of 10.5kW

Specification	
Supply Voltage / Current	3 Phase + E, 400V, 23A $\pm 15\%$ (Supplied with 5 Pin 32A Plug)
Frequency	50/60 Hz
Output Voltage / Current	0-60V / 180A, 65V / 160A continuously adjustable, CV/CC
Load Type	Standard 60V, 48V or 30V ceramic heating elements.
Supply Protection Fuse	25A
Temperature Sensor	Thermocouple - type K
Data Recording Range	-40°C to 1350°C
Temperature Control Range	-25°C to 1200°C
Alarm	Two adjustable - (1) deviation SV/PV and (2) set temperature reached
Fault Detection	Thermocouple disconnection, overload, overheating, output short circuit etc.
Multizone control	Up to 9 units can be linked to follow an single profile from the master unit.
Operating Temperature Protection	-20°C to 40°C (with a capacity limit to 50°C)
Case	Mild steel blue powder coated (stainless steel version - GHT 1235)
Dimensions	170mm x 370mm x 405mm
Weight	17 kg
Design Standards	EN 60519-1 ED. 4, EN 60519-2 ED. 2, EN 55011 ED. 4, EN61000

Recommended Accessories for a full set

Cables and Heaters	Thermocouples and accessories	Banding, insulation
1 x GHT 6009 25mm ² Triple cable set with Dinse plugs	1 x GHT 4100 Globe Thermocouple Welder (GTW -V50)	1 x GHT 9301 Banding machine
1 x GHT 6104-BK Four way splitter (Black)	1 x GHT 9208 100m roll of high density Thermocouple wire	2 x GHT 9303 Roll of stainless steel banding (30m)
1 x GHT 6104-OR Four way splitter (Orange)	or 1 x GHT 9209 100m roll of standard density Thermo couple wire	1 x GHT 9304 Box of stainless steel clips (100 clips per box)
30V and 60 V Ceramic elements*	1 x GHT 9040 Thermocouple plug type K	1 x GHT 9305 Iron tie wire (25kg roll)
*(See details of our full range of heaters available in our catalogue)	1 x GHT 9312 Tub of thermocouple putty	1 x GHT 7000 7.2m roll of 96g/m ³ Superwool insulation, 25mm thickness

